1. - 17. (Canceled)

5

10

15

18. (Currently Amended) One or more computer-readable media comprising computer-executable instructions that perform the following when

executed by one or more computers:

presenting extensible markup language (XML) data of a node of a first

XML document in a user interface having:

a first portion to display the XML data in an electronic form

representation; and

another portion concurrently displayable with the first portion to

display the XML data in a hierarchal tree representation;

enabling one or more operations through interaction with a component in

the electronic form representation corresponding to the XML data;

receiving selection of an operation of the one or more operations; and

modifying the XML data of the first XML document corresponding to the

component in the electronic form based on the received operation, wherein:

the act of presenting comprises determining that the node is

identified in a first element in a second XML document; and

20

SBMC, p.s. 2 MS-306941.01

5

10

15

the act of enabling comprises determining that the operations are identified in a second element associated with the first element in the second XML document; and

the act of modifying the XML data causes modifications to the XML data to be concurrently reflected in the electronic form representation and the hierarchal view representation.

- 19. (Currently Amended) The media of claim 18, wherein the act of presenting comprises presenting a blank data-entry field in the electronic form representation.
- 20. (Currently Amended) The media of claim 18, wherein the act of presenting comprises presenting a data-entry field having content in the electronic form representation, the content contained in the node.
- 21. (Original) The media of claim 18, wherein the act of determining that the node is identified comprises determining that the first element comprises a character string of "xmlToEdit".

20

SBMC, p.s. 3 MS-306941.01

22. (Original) The media of claim 18, wherein the act of determining that the node is identified comprises determining that a location of the node matches an XPath expression determinable from a value of an attribute on the first element.

5

23. (Original) The media of claim 18, wherein the act of determining that the node is identified comprises determining that the first element comprises a character string of "item" and that a value associated with that character string is usable to determine an XPath expression matching a location of the node.

10

24. (Original) The media of claim 18, wherein the act of determining that the operations are identified comprises determining that the second element comprises a character string of "editWith".

15

25. (Original) The media of claim 18, wherein the act of determining that the operations are identified comprises determining that the second element comprises a character string of "component" and a value associated with the character string, and using the value to determine the operations.

20

SBMC, p.s. 4 MS-306941.01

26. (Original) The media of claim 18, wherein the act of presenting comprises determining that the second XML document comprises a namespace having a namespace resource indicator having a character string of either

5

10

15

"microsoft" or "infopath".

- 27. (Original) The media of claim 18, wherein the first XML document comprises data not represented with XML.
- 28. (Original) The media of claim 18, wherein the act of determining that the operations are identified comprises determining that the second element comprises an attribute indicating that the operations comprise insertion or deletion of the identified node, or of a sibling node to the identified node.
- 29. (Original) The media of claim 28, wherein the value of the attribute comprises a character string of "xCollection".
- **30.** (Original) The media of claim 28, wherein the value of the attribute comprises a character string of "xOptional".

20

SBMC, p.s. 5 MS-306941.01

31. (Original) The media of claim 28, wherein the act of determining that the operations are identified further comprises determining: (a) that the second element indicates that the operations comprise insertion of the nodes; and (b) a location where the nodes are to be inserted based on one or more character strings in the first element, the character strings being treatable as an XPath expression.

5

10

15

20

32. (Original) The media of claim 28, further comprising determining a location for the insertion with an XPath expression associated with a character string of "item" in the first element.

33. (Original) The media of claim 28, further comprising determining the identified node or the sibling of the identified node using a child element of the second element, the child element comprising a character string "chooseFragment."

34. (Original) The media of claim 33, further comprising determining a location for inserting the identified node or the sibling of the identified node using an XPath expression associated with an additional character string of the child element.

35. (Original) The media of claim 34, wherein the additional character string is associated with a character string "parent."

SBMC, p.s. 6 MS-306941.01

36. (Original) The media of claim 18, wherein the act of determining that the operations are identified comprises determining that the second element comprises an attribute indicating that the operations comprise addition to or

alteration of data within the identified node.

5

37. (Original) The media of claim 36, wherein the act of determining that the second element comprises the attribute comprises determining that a value of the attribute comprises a character string of "xField".

10

38. (Original) The media of claim 37, wherein the act of determining that the operations are identified further comprises determining that the second element comprises a second attribute having a character string of "type".

15

39. (Original) The media of claim 38, wherein the act of determining that the operations are identified further comprises determining that the second attribute is associated with a character string of "rich" and the act of enabling one or more operations comprises enabling creation and modification of rich-text-data within the identified node.

20

SBMC, p.s. 7 MS-306941.01

5

10

15

20

41. (Currently Amended) One or more computer-readable media comprising computer-executable instructions that perform the following when executed by one or more computers:

presenting, in a first portion of a user interface, a first extensible markup language (XML) document as an electronic form having one or more data-entry fields representing one or more nodes of the first XML document, the user interface including another portion concurrently displayable with the first portion to display the first XML document in a hierarchal tree representation; and

enabling an operation to be performed on one of the nodes through its dataentry field, wherein:

the one node is identified in an a 'xmlToEdit' element comprising a character string of "xmlToEdit" in a second XML document; and

the operation enabled to be performed on the one node is identified in a child element of the 'xmlToEdit' element, the child element comprising a character string of "editWith"; and

SBMC, p.s. 8 MS-306941.01

when performed, the operation enabled to be performed causes a modification of data corresponding to the one node in the first XML document, the modification being concurrently reflected in the electronic

5

42. (Currently Amended) The media of claim [[0]] 41, wherein the one node is identified by an XPath expression associated with a value of an "item" attribute in the 'xmlToEdit' element.

form and the hierarchal tree representation.

10

43. (Currently Amended) The media of claim [[0]] 41, wherein the operation to be performed is identified by a value of a "component" attribute in the child element.

15

44. (Currently Amended) The media of claim [[0]] 41, wherein the act of enabling the operation comprises enabling the operation only if the electronic form comprises a representation of a context node, and wherein the context node is identified in a "container" attribute of the 'xmlToEdit' element.

45

45. - 49. (Canceled)

20

SBMC, p.s. 9 MS-306941.01